


## Connection Units



### Description

This uniquely shaped range is easy to install, with coloured terminals, clear white terminal markings and is supplied in individual protective bags.

This wide range includes flex outlet and neon versions.

### Features

- unique slim profile with curved top and bottom edges
- concave rockers
- only one size 4mm screwdriver needed
- clear white markings
- colour coded terminals
- neon versions available
- neon leads enclosed
- fuse carrier can be locked in the out position
- 2 earth terminals
- terminals have large lead-ins
- 20 year guarantee

### Technical Specification

voltage rating	250Vac
current Rating	13A
contact gap	3mm

no user serviceable parts, except BS 1362 fuse links

### Standards

- BS 1363 Part 4 : 1995
- Fuses – BS 1362

### Range

unswitched	S1360
unswitched, neon	S1361
unswitched, front flex outlet	S1362
unswitched, neon & front flex outlet	S1363
unswitched, bottom flex outlet	S1364
switched	S1370
switched, neon	S1371
switched, front flex outlet	S1372
switched, neon & front flex outlet	S1373
switched, bottom flex outlet	S1374
Unswitched – 3A fuse	S1380
Unswitched, neon – 3A fuse	S1381

### Back Boxes

minimum recommended depth

	Flush 25mm	Dry lining 35mm	Surface 25mm
1g	DB162	DB2540	V1221

### Terminal Capacity

	2.5mm <sup>2</sup>	4mm <sup>2</sup>	6mm <sup>2</sup>	10mm <sup>2</sup>
L & N	4	3	2	1

**DETA**

Kingsway House, Laporte Way  
Luton, Beds LU4 8RJ

Tel. +44 1582 544 500 Fax: +44 1582 544 501  
Technical Helpline +44 1582 544 548